



F Compression connector 4.9

Premium 4.9 F connector in compression design with shielding values of ≥ 120 dB

EAN	Colour	Item no.
4019588100374	silver	0100/3337

TOP FEATURES

High-end F connector
100% waterproof

Operational up to 3 GHz
Suitable for COAXSAT 120-4.6 and 140-4.6
cables from TechniSat

Suitable for all RG6 coaxial cables 1.0/4.6
Installation with compression pliers
0000/3339 from TechniSat

ATTENUATION

10 MHz : 0,01
100 MHz : 0,01
450 MHz : 0,01
862 MHz : 0,01
1000 MHz : 0,02
2250 MHz : 0,02

RETURN LOSS

65 - 470 MHz : ≥ 38 dB
470 - 1800 MHz : ≥ 38 dB
1800 - 2450MHz : ≥ 35 dB

SHIELDING

30 - 1000 MHz : > 140 dB CoMeT
1000 - 2250 MHz : > 120 dB CoMeT

TECHNICAL DATA

Protection class : IPX8
Impedance : 75Ω
Diameter dielectric : max. 4,6 mm
Diameter with coating : 6,8 ... 7 mm

TRANSFER IMPEDANCE

5MHz : $< 2,5$
30 MHz : $< 2,5$

SCOPE OF DELIVERY

Pack: 100 piece