



F Compression connector 4.9

Premium 4.9 F connector in compression design with shielding values of ≥ 120 dB

EAN	Colour	Item no.
4019588100374	silver	0100/3337

TOP FEATURES

High-end F connector

100% waterproof

Operational up to 3 GHz

Suitable for COAXSAT 120-4.6 and 140-4.6 cables from TechniSat

Suitable for all RG6 coaxial cables 1.0/4.6

Installation with compression pliers 0000/3339 from TechniSat

ATTENUATION

10 MHz : 0,01

100 MHz : 0,01

450 MHz : 0,01

862 MHz : 0,01

1000 MHz : 0,02

2250 MHz : 0,02

RETURN LOSS

65 - 470 MHz : ≥ 38 dB

470 - 1800 MHz : ≥ 38 dB

1800 - 2450MHz : ≥ 35 dB

SHIELDING

30 - 1000 MHz : > 140 dB CoMeT

1000 - 2250 MHz : > 120 dB CoMeT

TECHNICAL DATA

Protection class : IPX8

Impedance : 75Ω

Diameter dielectric : max. 4,6 mm

Diameter with coating : 6,8 ... 7 mm

TRANSFER IMPEDANCE

5MHz : $< 2,5$

30 MHz : $< 2,5$

SCOPE OF DELIVERY

Pack: 100 piece